

US 11,601,013 B1

11

generated electrical power into a plurality of preparticles that include muons in electrical communication with said at least one leg of said tower;
wherein said transmitter associated with said tower is in electrical communication with said at least one transducer and is operative to wirelessly transmit said plurality of preparticles into ambient air surrounding said tower.
11. The system as in claim 10, wherein:
said at least one leg of said tower is a North tower leg mounted to said base member and extends upwardly, said rotation of said base member causing said North tower leg to face a true North magnetic pole, said North tower leg having a positive electrical charge;
said tower includes a South tower leg mounted to said base member and extending upwardly and having a negative electrical charge, said South tower leg being positioned opposite to and spaced apart from said North tower leg;

12

said tower includes a West tower leg and an East tower leg opposite said West tower leg, said West and said East tower legs being dipoles having no electrical charge; and
wherein said induction sphere is positioned centrally between said North, South, West, East tower legs so as to magnetically induce electrons to move from the magnetosphere to said cable.
12. The system as in claim 10, wherein said cable is positioned in a trench defined in the ground surface proximate said plurality of generators, said trench being devoid of any metal material.
13. The system as in claim 12, wherein said trench includes an excavation that is 16 feet deep and less than 6 feet wide and defining a flat bottom, said trench including a first layer of crushed and cleaned bauxite ore upon which said cable is positioned, said trench including a second layer of crushed and cleaned bauxite ore positioned atop said cable.

* * * * *